

QXJY.EX16089 - Centrifugal Fire Pumps, Split Case

Centrifugal Fire Pumps, Split Case

BRISTOL FIRE ENGINEERING L L C

AL QUOZ INDUSTRIAL AREA 3
PO BOX 74582
DUBAI, United Arab Emirates

EX16089

Fire pumps, single stage

Rated Capacity (gpm)	Size (in.)	Model Dsg	Rated Net Pressure Range (psi)	Approx Speed (rpm)	Max Working Pressure (psi)
300	5x3	BSP-125-270	117-159	2950	250
300	5x3	BSP-125-270	121-165	3000	250
400	5x3	BSP-125-270	115-157	2950	250
400	5x3	BSP-125-270	120-163	3000	250
450	5x3	BSP-125-270	114-155	2950	250
500	5x3	BSP-125-270	112-154	2950	250
500	5x3	BSP-125-270	117-160	3000	250
500	6x4	BSP-150-310	129-222	2950	260
500	6x4	BSP-150-310	139-230	3000	260
500	8x5	BSP-200-290	165-228	3550	280
500	6x4	BSP-150-370	238-293	2950	365
500	6x4	BSP-150-370	235-264	2800	365
500	6x4	BSP-150-370	202-226	2600	365
500	6x4	BSP-6x4x10HF	91-126	2950	217
500	6x4	BSP-6x4x10HF	130-178	3500	217
500	6x4	BSP-6x4x10HF	100-130	3000	217
750	6x4	BSP-6x4x10HF	85-121	2950	217
750	6x4	BSP-6x4x10HF	123-174	3500	217

750	6x4	BSP-6x4x10HF	93-125	3000	217
750	6x4	BSP-150-370	233-285	2950	365
750	6x4	BSP-150-370	228-256	2800	365
750	6x4	BSP-150-370	195-219	2600	365
750	8x5	BSP-200-365	222-271	3000	330
750	8x5	BSP-200-365	214-262	2950	330
750	8x5	BSP-200-365	193-236	2800	330
750	8x5	BSP-200-365	165-203	2600	330
750	6x4	BSP-150-310	125-223	2950	260
750	6x4	BSP-150-310	133-231	3000	260
750	8x5	BSP-200-290	165-228	3550	280
1000	8x6	BSP-8x6x18MF	152-238	3000	290
1000	8x6	BSP-8X6x18MF	147-230	2950	290
1000	8x6	BSP-8X6x18MF	153-182	2100	290
1000	6x4	BSP-150-370	224-277	2950	365
1000	6x4	BSP-150-370	219-248	2800	365
1000	6x4	BSP-150-370	186-212	2600	365
1000	8x5	BSP-200-365	218-268	3000	330
1000	8x5	BSP-200-365	210-259	2950	330
1000	8x5	BSP-200-365	188-233	2800	330
1000	8x5	BSP-200-365	161-199	2600	330
1000	8x5	BSP-200-290	155-222	3550	280
1000	8x5	BSP-200-290	161-201	3000	280
1000	6x4	BSP-150-310	117-218	2950	260
1000	6x4	BSP-150-310	123-226	3000	260
1000	8x5	BSP-200-290	155-194	2950	250
1000	6x4	BSP-6x4x10HF	76-112	2950	217
1000	6x4	BSP-6x4x10HF	114-166	3500	217
1000	6x4	BSP-6x4x10HF	84-117	3000	217
1000	10x8	BSP-10x8x21HF	87-149	1500	239
1000	10x8	BSP-10x8x21HF	113-203	1750	239

1000	10x8	BSP-10x8x29MF	174-222	1750	260
1250	8x6	BSP-8x6x18MF	149-231	3000	290
1250	8x6	BSP-8X6x18MF	144-222	2950	290
1250	8x6	BSP-8X6x18MF	150-179	2100	290
1250	10x8	BSP-10x8x21HF	86-149	1500	239
1250	10x8	BSP-10x8x21HF	111-202	1750	239
1250	10x8	BSP-10x8x29MF	171-218	1750	260
1250	8x5	BSP-200-290	148-217	3550	280
1250	8x5	BSP-200-290	153-199	3000	280
1250	8x5	BSP-200-290	147-191	2950	250
1250	8x5	BSP-200-365	213-263	3000	330
1250	8x5	BSP-200-365	205-254	2950	330
1250	8x5	BSP-200-365	183-227	2800	330
1250	8x5	BSP-200-365	156-194	2600	330
1500	8x6	BSP-8x6x18MF	145-221	3000	290
1500	8x6	BSP-8X6x18MF	140-212	2950	290
1500	8x6	BSP-8X6x18MF	147-176	2100	290
1500	8x5	BSP-200-290	144-193	3000	280
1500	8x5	BSP-200-290	138-184	2950	250
1500	8x5	BSP-200-365	206-257	3000	330
1500	8x5	BSP-200-365	198-248	2950	330
1500	8x5	BSP-200-365	177-221	2800	330
1500	8x5	BSP-200-365	150-188	2600	330
1500	10x8	BSP-10x8x21HF	84-148	1500	239
1500	10x8	BSP-10x8x21HF	110-202	1750	239
1500	10x8	BSP-10x8x29MF	167-214	1750	260
2000	8x6	BSP-8x6x18MF	135-197	3000	290
2000	8x6	BSP-8X6x18MF	129-188	2950	290
2000	8x6	BSP-8X6x18MF	140-168	2100	290
2000	10x8	BSP-10x8x21HF	78-144	1500	239
2000	10x8	BSP-10x8x21HF	105-200	1750	239

2000	10x8	BSP-10x8x29MF	122-209	1450	260
2000	10x8	BSP-10x8x29MF	160-207	1750	260
2000	10x8	BSP 10x8x26MF	138-199	1490	260
2000	10x8	BSP 10x8x26MF	125-198	1760	260
2500	10x8	BSP 10x8x26MF	130-187	1490	260
2500	10x8	BSP 10x8x26MF	118-189	1760	260
2500	8x6	BSP-8X6x18MF	128-158	2100	290
2500	10x8	BSP-10x8x29MF	114-198	1450	260
2500	10x8	BSP-10x8x29MF	151-196	1750	260
3000	10x8	BSP-10x8x29MF	136-188	1450	260
3000	10x8	BSP-10x8x29MF	140-185	1750	260
3000	10x8	BSP 10x8x26MF	120-176	1490	260
3000	10x8	BSP 10x8x26MF	110-181	1760	260

Trademark and/or Tradename:

BRISTOL

Last Updated on 2021-05-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"



QYZS.EX3971 Pump Controllers, Fire

[Page Bottom](#)

Pump Controllers, Fire

[See General Information for Pump Controllers, Fire](#)

TORNATECH INC

EX3971

#132

7075 PLACE ROBERT-JONCAS

ST LAURENT, QC H4M 2Z2 CANADA

Fire Pump Controllers: Model AF, AFP, AFR, AFY, ATF, ATR, ATP or ATY followed by C or N, followed by additional suffixes. All of the above controllers are suitable for use on circuits capable of delivering high fault currents. The withstand ratings are as follows:

Circuit Breaker	Max V AC	Max Short Circuit Current RMS Symmetrical Amps
MZMH6-63, -100,	208; 240	25000; 42,000
-160, -250		
MZMH6-63, -100,	480	65,000
160, -250		

The controllers provided with Automatic Transfer Switches are suitable for use on circuits capable of delivering high fault currents. The withstand rating of the normal power source side is determined by the transfer switch as indicated below:

ASCO Transfer Switch	Max Controller Short Circuit Withstand Rating
9403704	22KA, 480 VAC Max
94031004	22KA, 480 VAC Max
94032604	35KA, 480 VAC Max

The withstand ratings for the alternate power source side will be dependent upon the ratings of the external circuit breaker provided. But in no case will they exceed those of the normal power source side.

Model AL or AL1 followed by additional suffixes.

All of the above controllers are suitable for use on circuits capable of delivering high fault currents. The withstand ratings are as follows:

Circuit Breaker	Max V AC	Max Short Circuit Current RMS Symmetrical Amps
NZM6B-63,	480	25,000
-100, -160		

The controllers provided with automatic Transfer Switches are suitable for use on circuits capable of delivering high fault currents. The withstand rating of the entire controller is determined by the transfer switch as indicated below:

ASCO Transfer Switch	Max Controller S. C. Withstand Rating
9403704	22KA, 480 VAC Max
94031004	22KA, 480 VAC Max
94032604	25KA, 480 VAC Max

The withstand ratings for the alternate power source side will be dependent upon the ratings of the external circuit breaker provided. But in no case will they exceed those of the normal power source side.

Authorities having jurisdiction should be consulted in all cases.

Model FPD Series controller for engine-driven centrifugal fire pumps.

Models FPA, FPP, FPR, FPS, FPV, FPW, FPY, VPA, VPR, and VPS may be followed by additional suffixes. The withstand ratings are as follows:

Withstand Ratings of Controllers Without Transfer Switch:

Short Circuit Withstand Ratings (Ampere Symmetrical)		

VOLTAGE	STANDARD	OPTIONAL HIGH
200 to 480 V	100,000A RMS	150,000A RMS
575 to 600 V	50,000A RMS	100,000A RMS

Model ATG or VPG. The controllers provided with Automatic Transfer Switches are suitable for use on circuits capable of delivering high fault currents. The withstand rating of the normal power side is the same as the withstand ratings of controllers without transfer switches. The withstand rating of the alternate power side is determined by the transfer switch as indicated by the following tables:

Withstand ratings of controllers with 120 A Tornatech Inc. Transfer Switch

200-208V 50/60 Hz MAX HP	230-240V 50/60 Hz MAX HP	380-416V 50/60 Hz MAX HP	440-480V 50/60 Hz MAX HP	600V 60Hz MAX HP	Withstand Rating (A)
40	40	—	—	—	65,000
—	—	60	75	—	25,000
—	—	—	—	100	18,000

Withstand Ratings For Controllers with Ascoelectric Transfer Switches

Transfer Switch (A)	200-208V 50/60 Hz Max HP	230-240V 50/60 Hz Max HP	Withstand Rating		Specific** Withstand Rating (A)
			(A)	Time (Cycles)	
100	30	30	10000	1.5	22000
150	50	50	1000	1.5	22000
400	150	150	35000	3	42000
600	N/A	N/A	50000	3	65000

**Tested and found suitable for 100kA

Withstand Ratings for Controllers with Ascoelectric Transfer Switches, Continued

Transfer Switch (A)	600V 60 Hz Max HP	Withstand Rating		Specific Withstand Rating (A)		
		(A)	Time (Cycles)			
100	75	10000	1.5	N/A		
150	150	1000	1.5	N/A		
400	400	22000	3	N/A		
600	N/A	N/A	N/A	N/A		
Model ATU:	Normal Power Side:	Same as withstand rating of controller without transfer switch.				
	Alternate Power Side:	Same as withstand rating of controller without transfer switch.				
Model FPL, GPL:		Limited Service controllers with withstand ratings as follows:				
Short Circuit Withstand Ratings of Limited Service Controllers Without Transfer Switches						
VOLTAGE		STANDARD		OPTIONAL HIGH		
200 to 480 V		25,000 A RMS		65,000 A RMS		
575 to 600 V		18,000 A RMS		25,000 A RMS		
Model LTG, GLG:		Automatic transfer switch for connection to a generator set.				
Model LTU, GLU:		Automatic transfer switch for connection to a 2 nd utility.				

Withstand ratings of Controller with transfer switch Model FPAT (Tornatech):

Model LTG:	Normal Power Side:	Same as withstand rating of controller without transfer switch.		
	Alternate Power Side:	Withstand rating only applies when the generator		
		set is protected by a molded case circuit breaker		
TRANSFER SWITCH AMPERES		200-480 V H.P.	WITHSTAND RATING AMPERES	
120		30	25,000	

TRANSFER SWITCH AMPERES		600 V H.P.	WITHSTAND RATING AMPERES	
120		30	18,000	
Model LTU:	Normal Power Side:	Same as withstand rating of controller without transfer switch.		
	Alternate Power Side:	Same as withstand rating of controller without transfer switch.		

Withstand ratings of controller with transfer switch Model 940 (Ascolectric):

Model LTG:	Normal Power Side:	Same as withstand rating of controller without transfer switch.		
	Alternate Power Side:	Withstand rating only applies when the generator set is protected		
		by a molded case circuit breaker not exceeding the ampere rating of		
		the transfer switch.		
Transfer Switch A	200-480 V Max HP	Withstand Rating		Specific Withstand Rating A
		A	Time	
120	30	10,000	1.5	22,000
Transfer Switch A	600 V Max HP	Withstand Rating		Specific Withstand Rating A
		A	Time	
120	30	10,000	1.5	N/A
Model LTU:	Normal Power Side:	Same as withstand rating of controller without transfer switch.		
	Alternate Power Side:	Same as withstand rating of controller without transfer switch.		

Models CPA, CPP, CPR, CPS, CPV, CPW, CPY, may be followed by additional suffixes. The withstand ratings are as follows:

Withstand ratings of controllers without transfer switch:

Short circuit withstand ratings (ampere symmetrical)			
voltage		standard	optional
200 to 480 V		100 kA	150 kA
575 to 600 V		50 kA	100 kA

Model CPU - The controllers provided with automatic transfer switches are suitable for use on circuits capable of delivering high fault currents. The withstand rating of the normal power side and the alternate power side is the same as the withstand ratings of controllers without transfer switches.

Model CPU

Short circuit withstand rating for alternate power circuit with transfer switch (RMS Symmetrical)			
V		Standard	High (optional)
200 to 480 V		100 kA	150 kA
575 to 600 V		50 kA	100 kA

Model **GPD** Series controller for engine-driven centrifugal fire pumps.

Battery chargers, BCE10, followed by 12 or 24, followed by 120 or 220.

Fire pump controllers, Models GPA, GPP, GPR, GPS, GPV, **GPY** and GPW.

Transfer switch, Model GPU.

Last Updated on 2013-01-03

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".



UL Product iQ
UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

NOW AVAILABLE

[➤ LEARN MORE](#)

QXZF.EX5190 Fire Pump Motors

If you notice a change to your QXZF Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Fire Pump Motors

[See General Information for Fire Pump Motors](#)

REGAL BELOIT AMERICA INC

EX5190

1946 W Cook Rd

Fort Wayne, IN 46818 USA

Model No.	Output	Hz/DC	Volts	FL Amps	Service Factor	Poles	Number of Speeds	RPM	Phases	Ins Class	Prot. Type	Rated Ambient (°C)
(click on a model number to see complete product details)												
143T Frame ODP	0-5hp	60	0-600	-	1 - 1.15	4	-	3600	3	F	-	55
	0-5hp	50	0-600	-	1 - 1.15	4	-	3000	3	F	-	55
	0-5hp	60	0-600	-	1 - 1.15	2	-	1800	3	F	-	55
	0-5hp	50	0-600	-	1 - 1.15	2	-	1500	3	F	-	55
145T Frame ODP	0-5hp	60	0-600	-	1 - 1.15	4	-	3600	3	F	-	55
	0-5hp	50	0-600	-	1 - 1.15	4	-	3000	3	F	-	55
	0-5hp	60	0-600	-	1 - 1.15	2	-	1800	3	F	-	55
	0-5hp	50	0-600	-	1 - 1.15	2	-	1500	3	F	-	55
182T	2hp	50	190/380	6/3	-	2	-	3000	3	H	-	55
	3hp	60&50	190/380	9/4.5	-	2	-	3600&3000	3	H	-	55
	3hp	60&50	200/400	8.6/4.3	-	2	-	3600&3000	3	H	-	55
	3hp	60&50	208/416&208/415	8.2/4.1	-	2	-	3600&3000	3	H	-	55
	3hp	60&50	220/440	7.8/3.9	-	2	-	3600&3000	3	H	-	55
	3hp	60&50	220/380	9/4.5&7.8/4.5	-	2	-	3600&3000	3	H	-	55
	3hp	60&50	230/460	7.4/3.7	-	2	-	3600&3000	3	H	-	55
	3hp	60&50	240/480	7/3.5&7.2/3.6	-	2	-	3600&3000	3	H	-	55
	3hp	60/50	575	3	-	2	-	3600/3000	3	H	-	55
	2hp	50/60	190/380	7.4/3.7	-	4	-	1500	3	H	-	55
	2hp	50	200/400	7.8/3.9	-	4	-	1500	3	H	-	55
	2hp	50	208/415	8.8/4.4	-	4	-	1500	3	H	-	55
	3hp	60&50	190/380	10.4/5.2&9.8/4.9	-	4	-	1800&1500	3	H	-	55
	3hp	60&50	200/400	9.8/4.9&9.4/4.7	-	4	-	1800&1500	3	H	-	55
	3hp	60&50	208/416&208/415	9.6/4.8&9/4.5	-	4	-	1800&1500	3	H	-	55
	3hp	60&50	220/440	9/4.5&8.4/4.2	-	4	-	1800&1500	3	H	-	55
	3hp	60&50	220/380	10.4/5.2&8.5/4.9	-	4	-	1800&1500	3	H	-	55

	408kW												
Model PRODUCT; followed by 0 through 9 or A through Z; followed by 0 through 9 or A through Z; followed by LM; followed by a five or six digit number; may or may not be followed by one or two letters A through ZZ; may or may not be followed by one or two letters A through Z; may or may not be followed by R; may or may not be followed by 0 through 999 or one or two letters A through Z; all followed by H.													
	0.75-408kW	50/60	220-690	-	1.15	2/4	1	-	3	F	-	55	
Models 0 through 9 or any letter A through Z; followed by any Letter A through N; followed by 143T, 145T, 182T, 184T, 213T, 215T, 254T, 256T, 284T, 284TS, 286T, 286TS, 324T, 324TS, 326T, 326TS, 364T, 364TS, 365T, 365TS, 404T, 404TS, 405T, 405TS, 444T, 444TS, 445T, 445TS, 447T, 447TS, 449T or 449TS; followed by the Letter T; followed by the Letter F; followed by the Letter C; followed by the Letter D; followed by one to five Digits 0 through 99999; which may or may not be followed by any Letter A through Z; which may or may not be followed by Letter A through Z; which may or may not be followed by the letter R; followed by one to three digits 1 through 999; all followed by Letter H.													
	0.75-408kW	50/60	220-690	-	1.15	2/4	1	-	3	F	-	55	
Models 0 through 9 or any letter A through Z; followed by any Letter A through N; followed by 143T, 145T, 182T, 184T, 213T, 215T, 254T, 256T, 284T, 284TS, 286T, 286TS, 324T, 324TS, 326T, 326TS, 364T, 364TS, 365T, 365TS, 404T, 404TS, 405T, 405TS, 444T, 444TS, 445T, 445TS, 447T, 447TS, 449T, or 449TS; followed by the Letter T; followed by the Letter F; followed by the Letter C; followed by Letter D; followed by one to five Digits 0 through 99999; which may or may not be followed by the addition of a dash followed by a one to six digit number; which may or may not be followed by any Letter A through Z; which may or may not be followed by Letter A through Z; all followed by letter H.													
	0.75-408kW	50/60	220-690	-	1.15	2/4	1	-	3	F	-	55	
Models T; followed by letter C; followed by a letter A; followed by three digits or letter or combination of both; followed by one digit 0 through 9; followed by a letter A through D; followed by one digit 0 through 9 or any Letter A through Z; followed by one digit 1 through 5; followed by one digit 1 through 9; followed by one digit 1 through 3; followed by one digit 0 through 9 or one letter A through Z; followed by one digit 0 through 9 or one letter A through Z; followed by one digit 0 through 9 or one letter A through Z.													
	0.75-408kW	50/60	220-690	-	1.15	2/4	1	-	3	F	-	55	

[Click here to view the Colombia Market Access Certification](#)

Trademark and/or Tradename: "2GREEN", "Century", "Century Electric", "EX5190", "EconoMaster", "Fasco", "Genteq", "HeatMaster", "LEESON", "LEESON ELECTRIC", "LEESON Electric", "Lincoln Motors", "Marathon", "Marathon Electric", "Marathon Generators", "Marathon Motors", "Morrill Motors", "Regal", "Sinya Motor", "Source 1",



Last Updated on 2018-06-19

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".

QXZF.EX5990 - FIRE PUMP MOTORS

Fire Pump Motors

See General Information for Fire Pump Motors

WEG EQUIPAMENTOS ELETRICOS SA

AV PREF WALDEMAR GRUBBA 3000

89256-900 JARAGUA DO SUL, SC BRAZIL

EX5990

Model No.	Output	Hz/DC	Volts	FL Amps	Service Factor	Poles	Number of Speeds	RPM	Phases	Ins Class	Prot. Type	Rated Ambient (°C)
(click on a model number to see complete product details)												
1 through 9 followed by U, followed by T, followed by 0 or E, followed by D, F, I, J, L, P, 2, ?,] or +, followed by C or F, followed by A, D, G, H, I, J, K, M, N, P, 3 or 4, followed by I or N, followed by M, P or X, followed by H, N, P, T, or X, followed by three digits, followed by 02, 04 or 06, may be followed by E, O, or P, may be followed by additional letters or numbers, may be followed by Z. (v)												
	1-500hp	50, 60, 50, 60, 50, 60	190-600	-	1.0-1.15	2, 2, 4, 4, 6, 6	1	3000, 3600, 1500, 1800, 1000, 1200	3	H	-	40
254, 254/6, 256, "W40" Series	25hp, 20hp, 25hp, 20hp, 15hp, 10hp	60, 50, 60, 50, 60, 60	600	-	-	2, 2, 4, 4, 4, 4	-	3600, 3000, 1800, 1500, 1200, 1000	3	F, H	-	60
284, 284/6, 286, "W40" Series	40hp, 30hp, 40hp, 30hp, 25hp, 20hp	60, 50, 60, 50, 60, 60	600	-	-	2, 2, 4, 4, 4, 4	-	3600, 3000, 1800, 1500, 1200, 1000	3	F, H	-	60
324, 324/6, 326, "W40" Series	60hp, 50hp, 75hp, 60hp, 50hp, 40hp	60, 50, 60, 50, 60, 60	600	-	-	2, 2, 4, 4, 4, 4	-	3600, 3000, 1800, 1500, 1200, 1000	3	F, H	-	60
364, 364/5, 365, "W40" Series	100hp, 75hp, 100hp, 75hp, 60hp, 50hp	60, 50, 60, 50, 60, 60	600	-	-	2, 2, 4, 4, 4, 4	-	3600, 3000, 1800, 1500, 1200, 1000	3	F, H	-	60
404, 404/5, 405, "W40" Series	150hp, 125hp, 150hp, 100hp, 100hp, 75hp	60, 50, 60, 50, 60, 60	600	-	-	2, 2, 4, 4, 4, 4	-	3600, 3000, 1800, 1500, 1200, 1000	3	F, H	-	60

[illegible]

	1-300hp, 1-350hp, 1-400hp, 1-500hp, 1-350hp, 1-500hp	50, 60, 50, 60, 50, 50	190-600	-	1.15	2, 2, 4, 4, 6, 6	1	3000, 3600, 1500, 1800, 1000, 1200	3	H	-	50
	1-350hp, 1-300hp, 1-400hp, 1-500hp, 1-350hp, 1-500hp	60, 50, 50, 60, 50, 60	190-600	-	-	2, 2, 4, 4, 6, 6	1	3600, 3000, 1500, 1800, 1000, 1200	3	F, H	-	50
W22 Series, Motor Model T; followed by E; followed by 1B, 1E, 1F, 1G, 1H, 1I, 1J; followed by C or F; followed by 04, 0D, 0G, 0H, 0I, 0J, 0K, 0L, 0M, 0N, 0P, 0Q, 0R, 0T, 0U or 0X; followed by 0A, 0C, 0D, 0E, 0F, 0H, 0I, 0J, 0K, 0L, 0M, 0N, 0P, 0R, 0S, 0T, 0W, or 0X; followed by 00001, 00003 or 00009; followed by 00001 through 99999, and may or may not be followed by 50. + (v)												
	1-300hp, 1-350hp, 1-400hp, 1-500hp, 1-350hp, 1-500hp, 40hp, 30W	50, 60, 50, 60, 50, 60, 60	190-600, 190-600, 190-600, 190-600, 190-600, 190-600, 480	, , , , , , 43.8	-	2, 2, 4, 4, 6, 6, 2	1	3000, 3600, 1500, 1800, 1000, 1200, 3600	3	F, H	-	50
W22 Series, Motor Model T; followed by E; followed by 1B, 1E, 1F, 1G, 1H, 1I, 1J; followed by C, F or A; followed by 04, 0D, 0G, 0H, 0I, 0J, 0K, 0L, 0M, 0N, 0P, 0Q, 0R, 0T, 0U or 0X; followed by 0A, 0C, 0D, 0E, 0F, 0H, 0I, 0J, 0K, 0L, 0M, 0N, 0P, 0R, 0S, 0T, 0W, or 0X; may be followed by 00001, 00003 or 00009; may be followed by 00001 through 99999, and may or may not be followed by 50. + (v)												
	1-300hp, 1-350hp, 1-400hp, 1-500hp, 1-350hp, 1-500hp	50, 60, 50, 60, 50, 60	190-600	-	1.15	2, 2, 4, 4, 6, 6	1	3000, 3600, 1500, 1800, 1000, 1200	3	H	-	50

(v) - Voltage range details: 190, 200, 208, 220, 230, 240, 380, 400, 415, 440, 460, 480, 525, 575, 600, 115/208-230, 208-230, 208-230/460, 190/380, 200/400, 230/460/380, 380-415/460, 220/380/440, 230/400, 220/380, 380/440//380-400-415, 380/440-460//380-400-415.

+ - The motor is also evaluated as Inverter Duty Motors.

[Click here to view the Colombia Market Access Certification](#)

Trademark and/or Tradename: 

Last Updated on 2019-02-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

QYLU.EX6155 - Internal-combustion Engines for Driving Stationary Fire Pumps

Internal-combustion Engines for Driving Stationary Fire Pumps

[See General Information for Internal-combustion Engines for Driving Stationary Fire Pumps](#)

CLARKE FIRE PROTECTION PRODUCTS LTD
GRANGE WORKS
LOMOND RD
COATBRIDGE, ML5 2NN UNITED KINGDOM

EX6155

DIESEL ENGINES RATED AT SPECIFIC SPEEDS

Model	No. of Cylinders	Rated HP	Rated Speed (rpm)
JU4H-UF04	4	50	2350
	4	55	2600
	4	60	2800
	4	60	3000
JU4H-UF10	4	41	1760
	4	51	2100
	4	55	2350
JU4H-UF12	4	55	2350
	4	59	2600
JU4H-UF14	4	55	2350
	4	59	2600
	4	70	2800
	4	71	3000
JU4H-UF20	4	60	1760
	4	67	2100
	4	72	2350
JU4H-UF22	4	72	2350

	4	75	2600
JU4H-UF24	4	72	2350
	4	75	2600
	4	80	2800
	4	83	3000
JU4H-UF30	4	64	1760
	4	79	2100
	4	85	2350
JU4H-UF32	4	85	2350
	4	85	2600
JU4H-UF34	4	85	2350
	4	85	2600
	4	104	2800
	4	115	3000
JU4H-UFH8	4	63	1470
	4	73	1760
JU4H-UFH0	4	73	1760
	4	88	2100
	4	98	2350
JU4H-UFH2	4	98	2350
	4	99	2600
JU4H-UF40	4	94	1760
	4	105	2100
	4	106	2350
JU4H-UF42	4	106	2350
	4	106	2600
JU4H-UF50	4	79	1470
	4	110	1760
	4	130	2100
	4	127	2350
JU4H-UF52	4	127	2350

	4	127	2600
JU4H-UF54	4	122	2350
	4	139	2600
	4	145	2800
	4	145	3000
JU4H-UF58	4	79	1470
	4	110	1760
JU4H-UFJ4	4	130	2800
	4	130	3000
JU4R-UF09	4	39	1760
	4	48	2100
	4	52	2350
JU4R-UF11	4	52	2350
	4	55.5	2600
JU4R-UF13	4	53	2350
	4	56.5	2600
	4	66.5	2800
	4	66.5	3000
JU4R-UF19	4	58.5	1760
	4	64.5	2100
	4	68	2350
JU4R-UF21	4	68	2350
	4	70.5	2600
JU4R-UF23	4	70	2350
	4	72.5	2600
	4	76.5	2800
	4	78	3000
JU4R-UF40	4	94	1760
	4	105	2100
	4	106	2350
JU4R-UF49	4	106	1760