

# UL/FM Certificates



# Certificate of Compliance

This certificate is issued for the following:

**Angle and Straightaway Hose Valves**

**KM300**

**Prepared for:**

**Kirmary International LLC**

91 Linden Ave

Irvington Township, New Jersey 07111

USA

Approval Standard: FM 1521, 1522 (December 2014)

Approval Identification: PR465870

Approval Granted: 3 May 2023

To verify the availability of the Approved product, please refer to [www.approvalguide.com](http://www.approvalguide.com)

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

A handwritten signature in black ink, appearing to read 'D.B. Fuller', written over a horizontal line.

David B. Fuller

VP, Manager – Fire Protection

FM Approvals

1151 Boston-Providence Turnpike

Norwood, MA 02062



*Member of the FM Global Group*



## VTSR.EX29020 - Hose Valves

## Hose Valves

**Kirmary International LLC**

EX29020

91 Linden Ave  
Irvington, NJ 07111-2562 United States

Angle types, 1-1/2, with female/female (NPT/NPS) and female/male (NPS) ends. for a maximum working pressure of 300 psi, for use on a fire hose rack assembly, or as a fire department outlet connection, Model(s) **KM300**

Angle types, 2-1/2 in., with female/female (NPT/NPS), female/male (NPS), Female NPT/Male NYC, GRV by Male NH, GRV by Male NYC and Male NH by Male NYC for a maximum working pressure of 300 psi, for use on a fire hose rack assembly, or as a fire department outlet connection, Model(s) KM300

Trademark and/or Tradename:



, "KIRMARY"

Last Updated on 2023-04-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."



# Certificate of Compliance

This certificate is issued for the following:

**Fire Department Connections**

**KM100**

**Prepared for:**

**Kirmary International LLC**

91 Linden Ave

Irvington Township, New Jersey 07111

USA

Approval Standard: FM 1530 (November 2016)

Approval Identification: PR465870

Approval Granted: 3 May 2023

To verify the availability of the Approved product, please refer to [www.approvalguide.com](http://www.approvalguide.com)

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

A handwritten signature in black ink, appearing to read 'D.B. Fuller', written over a horizontal line.

David B. Fuller

VP, Manager – Fire Protection

FM Approvals

1151 Boston-Providence Turnpike

Norwood, MA 02062



*Member of the FM Global Group*



# KM100 - Fire Department Connections

## Fire Department Connections

File Number: EX29019

### COMPANY

**Kirmary International LLC**

91 Linden Ave  
Irvington, NJ 07111-2562 United States

### MODEL INFO

**KM100**

Exposed Type

PRODUCT INFORMATION				
Pattern	Size, in.	Inlet End Type	Outlet End Type	Rated Pressure, psig (kPa)
Straightway	2-1/2 x 2-1/2 x 4	NST	NPT	300 (2070)



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."



# Certificate of Compliance

This certificate is issued for the following:

**Sprinkler System Alarm Test Devices**

**KM200**

**Prepared for:**

**Kirmary International LLC**

91 Linden Ave  
Irvington Township, New Jersey 07111  
USA

Approval Standard: FM 1625 (December 2009)

Approval Identification: PR465870

Approval Granted: 3 May 2023

To verify the availability of the Approved product, please refer to [www.approvalguide.com](http://www.approvalguide.com)

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

A handwritten signature in dark ink, appearing to read 'D.B. Fuller', written over a horizontal line.

David B. Fuller  
VP, Manager – Fire Protection  
FM Approvals  
1151 Boston-Providence Turnpike  
Norwood, MA 02062



*Member of the FM Global Group*



# KM200 - Drain Fittings, Special Type

## Drain Fittings, Special Type

File Number: EX29017

### COMPANY

**Kirmary International LLC**

91 Linden Ave

Irvington, NJ 07111-2562 United States

### MODEL INFO

**KM200**

PRODUCT INFORMATION		
Size, in.	Nominal K-Factor, gpm/v(psi) [L/min/v(kPa)]	Rated Pressure, psi (kPa)
1	5.6 (8)	300 (2070)
1-1/4	5.6 (8)	300 (2070)
1-1/2	5.6 (8)	300 (2070)
2	5.6 (8)	300 (2070)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."



# Certificate of Compliance

This certificate is issued for the following:

**Quick Opening Valves 1/4 Inch Through 2 Inch Nominal Size**

**KM250**

**Prepared for:**

**Kirmary International LLC**

91 Linden Ave

Irvington Township, New Jersey 07111

USA

Approval Standard: FM 1140 (October 1998)

Approval Identification: PR465870

Approval Granted: 3 May 2023

To verify the availability of the Approved product, please refer to [www.approvalguide.com](http://www.approvalguide.com)

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

A handwritten signature in black ink, appearing to read 'D.B. Fuller', written over a horizontal line.

David B. Fuller

VP, Manager – Fire Protection

FM Approvals

1151 Boston-Providence Turnpike

Norwood, MA 02062



*Member of the FM Global Group*





# KM250 - Valves, Trim and Drain

## Valves, Trim and Drain

File Number: EX29018

### COMPANY

**Kirmary International LLC**

91 Linden Ave  
Irvington, NJ 07111-2562 United States

### MODEL INFO

**KM250**

Ball

#### ATTRIBUTES AND RATINGS

Size, in. (mm)	Rated Pressure, psig (kPa)
1/4 (6.4);3/8 (9.5);1/2 (12.7);3/4 (19.1);1 (25.4);1-1/4 (31.8);1-1/2 (38.1)	600 (4136)
2 (50.8)	300 (2068)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

# KM150 - Valves, Trim and Drain

## Valves, Trim and Drain

File Number: EX29018

### COMPANY

**Kirmary International LLC**

91 Linden Ave  
Irvington, NJ 07111-2562 United States

### MODEL INFO

**KM150**

3-Way Globe

#### ATTRIBUTES AND RATINGS

Size, in. (mm)	Rated Pressure, psig (kPa)
1/4 (6.4)	600 (4136)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."